









Rehau AWADUCT PP COUPLERS, BALL JOINT, ADAPTORS AND “FLEX-CONNECT” UNIVERSAL CONNECTORS

ApprovalMark ISO Type 5 Product Certification Schedule AMI 71503 (AS/NZS 5065:2005)

Item	Model ID	Model Name	Product Description	Size range	Pic	Application
1	AWADUCT PP	KGEM PP SN10 (pipe dia/length)	KGEM pipes SN10 with socket coupler AWADUCT SN10 pipe with socket coupler and EPDM sealing rings according to DIN EN 1852 and AS/NZS 5065 Material: RAU- PP 2300 Colour: orange	110, 125, 160, 200, 250, 315, 400, 500, 630 (L = 1, 3 & 6m)		Wastewater pipes with RRJ. Can be used to supplement maintenance chambers i.e internal drops.
2	AWADUCT PP	KGGL PP SN10 (pipe dia/length)	KGGL pipes SN10 Fusion plain ended AWADUCT SN110 FUSION plain-ended, according to DIN 1852 and AS/NZS 5065 Material: RAU-PP 2300 Colour: orange	110, 125, 160, 200, 250, 315, 400, 500, 630 (pipe length is not specified) DN 800 (L = 3m & 6m)		Wastewater pipes utilising electrofusion jointing Can be used to supplement maintenance chambers i.e internal drops. This product is suitable for installation without rubber ring joint connection to network pipes
3	AWADUCT PP	KGU PP (dia)	KGU sleeve coupler AWADUCT PP sleeve coupler with EPDM sealing rings Material: RAU-PP 2300 Colour: orange	110; 125; 160; 200; 250; 315; 400; 500; 630		Sleeve coupler Connection of the pipes to bases of MS, MC and MH
4	AWADUCT PP	KGMM PP (dia)	KGMM double socket coupler AWADUCT PP double socket coupler with EPDM sealing rings Material: RAU-PP 2300 Colour: orange	110; 125; 160; 200; 250;315; 400; 500; 630		Double socket coupler Connection of the pipes to bases of MS, MC and MH

Item	Model ID	Model Name	Product Description	Size range	Pic	Application
5	AWADUCT PP	Ball joint (dia) (Soc-Soc & Soc-Spi)	Ball joint AWADUCT PP ball joint <i>Infinite angle adjustment by $\pm 7.5^\circ$ horizontally or vertically</i> with EPDM sealing rings Material: RAU-PP 2300 Colour: orange	160 Soc-Soc, 160 Soc-Spi, 200 Soc-Soc, 200 Soc-Spi		Ball joint Flexible connection to achieve the angle (up to 7.5 in any direction) between pipe and base on site during installation.
6	AWADUCT PP	KGMM PP Vario (dia)	KGMM Vario double socket coupler <i>Infinite angle adjustment by $\pm 7.5^\circ$ horizontally or vertically</i> With EPDM sealing rings Material: RAU-PP 2300 Colour: orange	250 & 315		KGMM vario Flexible connection to achieve the angle (up to 7.5 in any direction) between pipe and base on site during installation.
7	AWADUCT PP	KGUS PP (dia)	KGUS adaptor KGUS adaptor from vitrified clay spigot end to plastic with EPDM sealing rings Material: RAU-PP 2300 Colour: orange	110, 125, 160		Adaptor from vitrified clay spigot end to plastic at the connection to base.

Item	Model ID	Model Name	Product Description	Type (clamping range)	Pic	Application
8	AWADUCT	Flex-Connect	AWADUCT FLEX-CONNECT PIPE COUPLER To connect sewer pipes Material: PP / EPDM / Stainless Steel / Q-TE-C Colour: Orange / Black / Silver	110, 125, 160, 200, 250, 315, 400, 500, 630		<p>A pipe coupler used for connecting socket-less sewer pipes and fittings of different outer diameters, wall thickness, materials or surface structures.</p> <p>It can be used to connect almost all rigid or flexible pipes.</p> <p>Smooth, ribbed or corrugated pipe can be connected to each other using Flex connect.</p> <p>It is suitable for connection of pipes and fittings made of ductile iron, cast iron, earthenware (VC), unplasticised polyvinyl chloride (uPVC), polypropylene (PP), polyethylene (PE), fibre-cement or glass reinforced polyester resin (UP-GFK)</p>